

2300 European Wax



Available
from stock
on ZipShip

Ribbon	Ribbon Type		Compatible Material	Print Speed	Temperature Resistance	Smear/Scratch Resistance	Chemical Resistance
2300	Wax	Standard	Uncoated/Coated Paper				
2100	Wax	High-Performance	Uncoated/Coated Paper				
3400	Wax/Resin	High-Performance	Uncoated/Coated Paper Matte Synthetics				
3200	Wax/Resin	Premium	Uncoated/Coated Paper Matte Synthetics				
4800	Resin	Performance	Matte/Gloss Synthetics				
5095	Resin	High-Performance	Matte/Gloss Synthetics				
5100	Resin	Premium	Matte/Gloss Synthetics				
Image Lock™	Resin	Specialist	Z-Xtreme™ 5000T				

Additional Features

- Economy general purpose wax ribbon
- Suitable for printing on uncoated and coated paper labels and tags
- Excellent print quality when printing normal or rotated barcodes
- Ability to print up to speeds of 304mm/sec (12ips) and 152mm/sec (6ips) for rotated barcodes
- Excels when used with Zebra desktop printers

Suggested Applications

- General purpose labelling
- Shipping and receiving
- Inventory tracking
- Warehousing and distribution
- Retail labels and tags

Technical Specifications

	Description
Colour	Black
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	8 microns
Scanning Capabilities	IR and Visible Light

Ribbon Compliance

Compliance	2300
REACH/ Substances of Very High Concern (SVHC)	✓
RoHS	✓
Dodd-Frank Act (Conflict Minerals)	✓
Toxic Substances Control Act of 1976	✓
Carcinogenic, Mutagenic and Reprotoxic, or Substances Toxic Substances 1976/769/ EC	✓
California Proposition 65	✓
FDA 21 CFR Part 175.300 – Indirect Food Contact – Resinous and Polymeric Coatings	✓
European Food Directive 1935/2004/EC	✓
Foodstuffs and Consumer Goods Act and LFGB approved	✓
Halogen free	✓
Latex free	
Animal derivatives free	
BP Free	✓

Stocked Sizes Available for the following Zebra Printers:

Desktop, mid-range and high-performance thermal printers, Zebra engines, other legacy Zebra printers
(Other widths/lengths are available on request subject to minimum order quantities and lead times)

Recommended Storage Conditions:

1 year duration when stored at 5°C to 35°C at 20% to 80% RH

2300 Barcode Scannability

The below scannability testing was performed on 140XiIII.

Label Facestock	Print Speed	Barcode	Lab Results
Uncoated paper labels and tags	Up to 304.8mm/sec	10 mil normal code	Typical ANSI Grade B
Semi-coated paper labels	Up to 304.8mm/sec	10 mil normal code	Typical ANSI Grade A
Coated paper labels and tags	Up to 304.8mm/sec	10 mil normal code	Typical ANSI Grade A
Uncoated paper labels and tags	Up to 152.4mm/sec	15 mil rotated code	Typical ANSI Grade A
Semi-coated paper labels	Up to 152.4mm/sec	15 mil rotated code	Typical ANSI Grade A
Coated paper labels and tags	Up to 152.4mm/sec	15 mil rotated code	Typical ANSI Grade A
Uncoated paper labels and tags	Up to 152.4mm/sec	10 mil rotated code	Typical ANSI Grade B
Semi-coated paper labels	Up to 152.4mm/sec	10 mil rotated code	Typical ANSI Grade B
Coated paper labels and tags	Up to 152.4mm/sec	10 mil rotated code	Typical ANSI Grade B

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

All products should be pre-tested to ensure they meet all intended requirements of specific end-use applications.

For testing of this ribbon on Zebra mid-range and high-performance printers please order part number 02300BK11005. For testing on other printer models, please contact your Supplies Specialist representative.

2300 European Wax

Economy General Purpose Ribbon

The 2300 European Wax Ribbon—a versatile and reliable solution for all your labeling needs. Designed as a standard wax ribbon, it is perfectly suited for use with both uncoated and coated paper labels and tags, ensuring adaptability across various applications. The 2300 Zebra Wax Ribbon delivers excellent print quality, whether you are printing standard or rotated barcodes, making it an ideal choice for businesses that require precision and clarity. Capable of achieving impressive print speeds of up to 304 mm per second (12 ips) for standard barcodes and 152 mm per second (6 ips) for rotated barcodes, this ribbon ensures efficiency without compromising on quality. It particularly excels when used with Zebra desktop printers, providing seamless integration and performance. Choose the 2300 Zebra Wax Ribbon for consistent, high-quality results in your labeling operations.



The perfect companion for your Zebra labels, tags, and printers

Not all ribbons are created as equal. There are hundreds of different ribbon formulations in the market. That is why Zebra's supplies R&D team has tested and selected only those ribbons that deliver the best print quality and durability. To get the Zebra name, each ribbon must pass a series of print quality and durability tests. When you purchase Zebra wax ribbons you can be rest assured that the print will be readable and scannable every time. Print will and can withstand the environmental conditions it is utilized in. Backcoating will not cause premature printhead failure.

To learn more, visit
www.zebra.com/ribbons

Specifications

Attributes

Color	Black
Base Film	Polyester
Base Film Caliper	4.5 microns
Total Caliper	8 microns
Scanning Capabilities	IR and Visible Light

Ribbon Compliance

REACH/ Substances of Very High Concern (SVHC)
RoHS
Dodd-Frank Act (Conflict Minerals)
Toxic Substances Control Act of 1976
Carcinogenic, Mutagenic and Reprotoxic, or Substances Toxic Substances
1976/769/ EC
California Proposition 65
FDA
21 CFR Part 175.300—Indirect Food Contact—Resinous and Polymeric Coatings
European
Food Directive 1935/2004/EC
Foodstuffs and Consumer Goods Act and LFGB approved
Halogen free
BP free
Latex free
Animal derivates free

Ribbon Type

Standard 2300 Wax	Compatible Material: Uncoated/Coated Paper Print Speed: Up to 304 mm/sec (12 ips)
High Performance 2100 Wax	Compatible Material: Uncoated/Coated Paper Print Speed: Up to 304 mm/sec (12 ips)
High Performance 3400 Wax Resin	Compatible Material: Uncoated/Coated Paper/Matte Synthetics Print Speed: Up to 203 mm/sec (8 ips)
Premium 3200 Wax/ Resin	Compatible Material: Uncoated/Coated Paper/Matte Synthetics Print Speed: Up to 254 mm/sec (10 ips)
Performace 4800 Resin	Compatible Material: Matte/Gloss Synthetics Print Speed: Up to 152 mm/sec (6 ips)
High-Performan ce 5095 Resin	Compatible Material: Matte/Gloss Synthetics Print Speed: Up to 203 mm/sec (8 ips)
Premium 5100 Resin	Compatible Material: Matte/Gloss Synthetics Print Speed: Up to 152 mm/sec (6 ips)
Specialist Image Lock™ Resin	Compatible Material: Z-Xtreme™ 5000T Print Speed: Up to 101 mm/sec (4 ips)

Product Performance and Suitability

Recommended storage conditions	1 year duration when stored at 5°C to 35°C at 20% to 80% RH
Stocked Sizes Available for the following Zebra Printers	Desktop, mid-range and high-performance thermal printers, Zebra engines, other legacy Zebra printers (other widths/lengths are available on request subject to minimum order quantities and lead times)
	For testing of this ribbon on Zebra mid-range and high-performance printers please order part number 02300BK11005. For testing on other printer models, please contact your Supplies Specialist representative

Markets and Applications

Retail

- Retail labels and tags

Transportation and Logistics

- Shipping and receiving
- General purpose labelling
- Distribution

Manufacturing

- Inventory tracking
- Warehouse